



GE-B050-2T-G4-MSTW/2.8/3.6mm

S265 2MP Outdoor IP66 Wi-Fi Smart IP Camera



Economic Series



KEY FEATURES

- up to 2MP(1920x1080@25fps)
- IR Range Up to 35 Meter
- Support 3D digital noise reduction
- Support low bit rate and low latency
- S265 efficient compression, saving bandwidth and storage space
- Built-in human detection algorithm, support human detection in complex environments
- Support dual light night vision
- Support ONVIF, SLINK protocol
- ICR filter-type automatic switching for real day and night monitoring
- Support built-in Microphone & Speaker, support TF Card Slot, support Wi-Fi
- Support automatic electronic shutter function to adapt to different monitoring environments





SPECIFICATIONS

Image	
Image Sensor	1/2.9", 2MP progressive scan ultra-low illumination CMOS GC4053
Main Stream	PAL: 2MP 1920x1080@25fps, 720P 1280X720@25fps NTSC: 2MP 1920x1080@30fps, 720P 1280X720@30fps
Sub Stream	PAL: D1(720*576)@25fps, VGA(640*480)@25fps, Q720P(640*360)@25fps, CIF 352X288@25fps, 320X240@25fps NTSC: D1(720*576)@30fps, VGA(640*480)@30fps, Q720P(640*360)@30fps, CIF 352X288@30fps, 320X240@30fps
Smart Function	Human detection
Min. Illumination	Color : 0.1Lux@F1.2; B&W : 0Lux@F1.2(IR on)
Lens	F1.6 2.8/3.6mm
IR Distance	30-35M (8 lamps)
Noise Reduction	3D noise reduction
WDR	DWDR (off / low / medium / high)
Mirror	Off / horizontal mirroring / vertical mirroring / 180 ° rotation
Image Setting	Brightness / contrast / sharpness / saturation / chroma
Human Detection	
Responding Speed	≤1s
Maximum Detection Frame Rate	5fps/s (color image)
Detection Area	Support specified area, default full screen
Shielded Area	Support 4 areas setting
Upload Method	Private protocol upload
Trigger Method	Video trigger
Video and Audio Coding	
Encoding Format	S265/H.265/H.264
Video Bit Rate	Fixed bit rate, variable bit rate(1280kbps-4Mbps)
Video Type	Composite stream / video stream
Audio Coding Standard	G.711U/64Kbps
Smart IR	Yes
Audio	Built-in Mic
TF Card Slot	Up to 512G, Micro SD (EXT3/EXT4) card local storage
Network Function	
Network Interface	1*RJ45 10M/100M self-adaptive LAN port
Network Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, NTP
Interface Protocol	ONVIF
WiFi	Support WiFi



General	
Web Client Language	English/Spanish/Korean/Chinese S/Chinese T/Italian/Turkish/ /Russian/Arabic/Vietnamese/German
Operation T/H	- 20°C ~ 50°C / 0 % -90 %
Waterproof	IP66
Power Supply	DC12V
Power Consumption	<10W (MAX)
Dimension (mm)	Equipment:96.19(W)×82(H)×181.37(L)mm Packing: 140mm(W)×115mm(H)255mm(L)
Weight/PCS (g)	N.W.: 460g Packing: 520g
Outside Carton	24pcs/carton; 510mm×380mm×330mm; Weight: 12.8kg

Design and specifications are subject to change for product improvements without prior notice