



GE-B050-2T-G4-PM /3.6mm

S265/H.265 2MP/3MP Bullet

Economic Series



KEY FEATURES

- Support dual light night vision
- IR Range Up to 50 Meter
- Up to 3MP(2304X1296@20fps), 2MP(1920x1080@25fps)
- Support built-in PoE , built-in Mic
- IP66
- Color : 0.1Lux@F1.2; B&W : 0Lux@F1.2(IR on)
- Support ONVIF, SLINK protocol
- S265/H.265 efficient compression, saving bandwidth and storage space
- Built-in human detection algorithm, support human detection in complex environments
- Operating Conditions - 20°C ~ 50°C / 0 % -90 %





SPECIFICATIONS

Image	
Image Sensor	1/2.9", 2MP progressive scan ultra-low illumination CMOS GC4053
Main Stream	PAL: 3MP 2304X1296@20fps, 2MP 1920x1080@25fps NTSC: 3MP 2304X1296@25fps, 2MP 1920x1080@30fps
Sub Stream	PAL: 25fps (704×576, 704×288, 640×360, 352×288) NTSC: 30fps (704×480, 704×240, 640×360, 352×240)
Smart Function	Human detection
Min. Illumination	Color : 0.1Lux@F1.2; B&W : 0Lux@F1.2(IR on)
Lens	F1.6 2.8/3.6mm
IR Distance	50M 6 dual light
Noise Reduction	3D noise reduction
WDR	DWDR (off / low / medium / high)
Mirror	Off / horizontal mirroring / vertical mirroring / 180 ° rotation
Image Setting	Brightness / contrast / sharpness / saturation / chroma
Human Detection	
Shielded Area	Support 4 areas setting
Upload Method	Private protocol upload
Trigger Method	Video trigger
Video and Audio Coding	
Encoding Format	S265/H.265/H.264
Video Bit Rate	Fixed bit rate, variable bit rate(1280kbps-4Mbps)
Video Type	Composite stream / video stream
Day & Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
Audio Coding Standard	G.711U/64Kbps
Audio	Built-in Mic
Network Function	
Network Interface	1*RJ45 10M/100M self-adaptive LAN port
Network Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, NTP
Interface Protocol	ONVIF
POE	Built-in PoE
General	
Web Client Language	English/Spanish/Korean/Chinese S/Chinese T/Italian/Turkish/ /Russian/Arabic/Vietnamese/German/Ukrainian
Operation T/H	- 20°C ~ 50°C / 0% -90 %
Waterproof	IP67
Dimension (mm)	Equipment: 73.55(W)×64.8(H)×202(L)mm (with bracket) Packing: 105mm(W)×92mm(H)210mm(L)
Weight/PCS (g)	N.W.: 280g Packing: 340g
Outside Carton	45pcs/carton; 615mm×540mm×300mm; Weight: 13kg