



GE-S1587/T6

Network Video Server



KEY FEATURES

Operating System

- Open Euler

External Interface

- 4 Network Interface
- 2 HDMI Interface
- 2 USB2.0; 2 USB3.0
- 1 PCIE 3.0

Disk Type

- Support 2.5" or 3.5" SATA

Hard Disk

- Equipped with 64GB SSD system disk and 4TB enterprise-class data disk
- Support a total of four 1T-8T disks

Cache

- 32GB max up to 64GB



SPECIFICATIONS

Software	
Pre-installed Software	Golden Eye VMS
Sub System	Video preview, Video playback, Video on the wall, Video preview (WEB version), Video playback (WEB version), Access Control, Vehicle Management Face Application, Passenger Flow Management, Attendance Management, etc.
Storage/Forwarding Performance	Video Storage: Not involved, check the centralized storage server Video Forwarding: Not involved, check the streaming media server
NTP Setting	Support NTP time synchronization
External Interface	
Network Interface	4
HDMI Interface	2
I/O Interface	1 RS-232
USB Interface	2 USB2.0; 2 USB 3.0
PCI Expansion Slot	1 PCIE 3.0 X16
Fan	4
Hard Disk	Equipped with 64 GB SSD system disk and 4 TB enterprise-class data disk, it supports a total of four 1T-8T disks
Disk Type	Supports 2.5"or 3.5" SATA
Controller	
Processor	Intel I7-9700E (8 cores 8 threads)
Product Overview	The standard configuration is 32GB (4x8G), providing four DDR4 memory slots with a capacity of up to 64 GB
Operating System	openEuler-22.03-LTS-SP1
Compression	
Video Compression	S+265; H.265; S+264; H.264
Audio Compression	G711A; G711U; ADPCM_DIV4
Stream Type	Video; Video & Audio
General Norm	
Key and Indicator Light	Power Off button + power indicator, Restart button, hard disk read/write indicator, alarm indicator, network 1 ACT indicator, network 2 ACT indicator
Power Supply	1 built-in power supply, AC100V~240V; 50Hz
Power	Power supply rating: 250W Peak value: 158W Average of the whole machine: 142W
Operating Temperature	5°C~40°C
Operating Humidity	10%~90% (No Condensation)
Noise	Startup noise: 60dB Runtime noise: 40dB
Dimension	671.2mm(L)×433mm(W)×43.5mm(H)

Design and specifications are subject to change for product improvements without prior notice

