



GE-S1732/T1

Streaming Media Server



KEY FEATURES

Bandwidth

- Access Bandwidth 2048 Mbps
- Forwarding Bandwidth 2048 Mbps

Interface Parameter

- 4 Ethernet Ports
- 1 VGA Port
- 2 USB2.0 Ports; 2 USB3.0 Ports

Cache

- 16GB



SPECIFICATIONS

Interface Parameter	
Network Interface	4 GB ethernet ports
Video Interface	1 VGA port
Hard Disk	Built-in 128GB SSD system disk Supports three 1T to 8T hard disks
Disk Type	Supports 2.5"or 3.5" SATA
USB Interface	2 front-end USB2.0 ports; 2 rear USB 3.0 ports
Bandwidth	•Access bandwidth: 2048Mbps •Forwarding bandwidth: 2048Mbps •Access IP: 2000 Access Channels. •Access IP: 1000 Access Channels: 1000(Onvif Protocol)
Controller	
Processor	64-bit multi-core processor
Cache	The standard configuration is 16GB with four DDR4 memory slots
Operating System	OpenEuler2203SP1
General Norm	
Key and Indicator Light	Power Off button + power indicator, Restart button, hard disk read/write indicator, alarm indicator, network 1 ACT indicator, network 2 ACT indicator
Power Supply	AC100V~AC240V; 50Hz
Power	250W
Operating Temperature	5°C~40°C
Operating Humidity	10%~90% (No Condensation)
Dimension	670mm(L)×433mm(W)×43.5mm(H)

Design and specifications are subject to change for product improvements without prior notice



DIMENSIONS (Unit: mm)

